



C.I.V. OFFSHORE & SHIPPING




Hijzen

Hijsketting en –samenstellen


hijsketting

- kortschalmige hijsketting
- grade 10, grade 8+, grade 8
- gecoat of verzinkt
- 6 mm tot 32 mm
- WLL 1,12 ton – 31.5 ton



topschalmen

- enkele topschalmen
- topschalmen v.v. sub-schalmen
- topschalmen v.v. inkorthaken
- kraanhaak-topschalm
- WLL 1,25 ton – 125 ton



haken

- ooghaken of gaffelhaken
- klephaken of zelfsluitende haken
- wartelhaken
- containerhaken
- rondstrophaken
- WLL 1,5 ton – 32 ton



Lasttabel hijscapaciteit

Chain dim.	1-leg		2-leg		3- & 4-leg		Choke hitch	
		β 0-45° α 0-90°	β 45-60° α 90-120°	β 0-45° α 0-90°	β 45-60° α 90-120°	β 0-45° α 0-90°	β 45-60° α 90-120°	
6	1.5	2.12	1.5	3.15	2.24	3.6	1.2	
8	2.5	3.5	2.5	5.2	3.7	2.7	2	
10	4.0	5.8	4	8.4	6	4.4	3.2	
13	6.7	9.5	6.7	14.0	10	7.4	5.3	
16	10	14	10	21.0	15	11	8	
20	16	22.4	16	33.6	24	17.6	12.8	
22	19	26.9	19.0	40.3	28.5	20.9	15.2	
26	27.0	38.2	27.0	57.3	40.5	29.7	21.6	

Safety factor 4:1. Working load limits are based upon equally loaded and disposed sling legs.

C.I.V. Offshore & Shipping

Haventerrein 3 • 1779 GS Den Oever • Nederland
T. (0227) 74 90 10 • F. (0227) 51 17 01 • info@civos.nl

www.civos.nl