




C.I.V. OFFSHORE & SHIPPING

Hoisting

Lifting chains and assemblies


lifting chains

- short link lifting chains
- grade 10, grade 8+, grade 8
- coated or galvanized
- 6 mm to 32 mm
- WLL 1,12 ton – 31.5 ton



master links

- single master links
- master links with sub-links
- master links with grab hooks
- crane hook master link
- WLL 1,25 ton – 125 ton



hooks

- eye hooks or clevis hooks
- latch hooks or self-closing safety hooks
- swivel hooks
- container hooks
- webbing and round sling hooks
- WLL 1,5 ton – 32 ton



capacity table

Chain dim.	1-leg	2-leg		3- & 4-leg		Choke hitch	
		β 0-45° α 0-90°	β 45-60° α 90-120°	β 0-45° α 0-90°	β 45-60° α 90-120°	β 0-45° α 0-90°	β 45-60° α 90-120°
6	1.5	2.12	1.5	3.15	2.24	1.6	1.2
8	2.5	3.5	2.5	5.2	3.7	2.7	2
10	4.0	5.8	4	8.4	6	4.4	3.2
13	4.7	9.5	6.7	14.0	10	7.4	5.3
16	10	14	10	21.0	15	11	8
20	16	22.4	16	33.6	24	17.6	12.8
22	19	26.9	19.0	40.3	28.5	20.9	15.2
26	27.0	38.2	27.0	57.3	40.5	29.7	21.6

Safety factor 4:1. Working load limits are based upon equally loaded and disposed sling legs.

C.I.V. Offshore & Shipping

Haventerrein 3 • 1779 GS Den Oever • The Netherlands

T. +31 227 74 90 10 • F. +31 227 51 17 01 • info@civos.nl

www.civos.nl